

Car Rear View Camera Specification

Sensor	CMOS I	CMOS II	CCD
Effective Pixel	510*492	656*492	510*582
Horizontal Sync Frequency	15625KHz	15625KHz	15625KHz
Vertical Sync Frequency	PAL 50Hz / NTSC 60 Hz	PAL 50Hz / NTSC 60 Hz	PAL 50Hz / NTSC 60 Hz
Scanning System	2:1Interlace	2:1Interlace	2:1Interlace
Sync System	Internal	Internal	Internal
AGC	Auto	Auto	Auto
BLC	Auto	Auto	Auto
Resolution	380 TV Lines	420 TV Lines	420 TV Lines
S/N Ratio	More Than 48dB	More Than 48dB	More Than 48dB
Current Consumption	No more 150mA	No more 150mA	No more 300mA
Power supply	DC12V±10%	DC12V±10%	DC12V±10%
Operating Temperature	-20℃ ∽ 60℃ RH95% MAX	-30℃ ∽ 80℃ RH95% MAX	-20℃ ∽ 60℃ RH95% MAX
Storage Temperature	-30℃ ∽ 60℃ RH95% MAX	-40℃ ∽ 85℃ RH95% MAX	-30℃ ∽ 60℃ RH95% MAX
Horizontal Angle	92°/110°	110°/160°	110°
Lens Angle	92°/120°	120°/170°	120°
Water-proof	IP67—IP68	IP67—IP68	IP67—IP68
Minimum Illumination	2Lux/F1.2(0Lux with Led)	0.5Lux/F1.2(0Lux with Led)	0.8Lux/F1.2(0Lux with Led)